

SALTILLO TILE

TILE SPECS THICKNESS: 3/4" PRICE: SALTILLO TILE PRICING DEPENDS ON TYPE AND FINISH

TILE	ITEM	SIZE	FINISH
	RECTANGULAR (TRADITIONAL)	4" x 4"	UNSEALED, SEALED STAINED / ANTIQUE
		8" x 8", 12" x 12", 16" x 16", 6" x 12"	UNSEALED, SEALED STAINED / ANTIQUE MAGNESE
	SUPER (ROUND EDGE)	8" x 8", 12" x 12", 16" x 16"	UNSEALED, SEALED STAINED / ANTIQUE MAGNESE
	ABANICO	6", 12"	UNSEALED, SEALED STAINED / ANTIQUE
	STAR	6"	UNSEALED, SEALED STAINED / ANTIQUE
	FLEUR DE LIS	4"	UNSEALED, SEALED STAINED / ANTIQUE
		8"	UNSEALED, SEALED STAINED / ANTIQUE MAGNESE
	DIAMOND	8"	UNSEALED, SEALED STAINED / ANTIQUE
	ESPAÑOLA	12"	UNSEALED, SEALED STAINED / ANTIQUE

TILE	ITEM	SIZE	FINISH
	PICKET	12"	UNSEALED, SEALED STAINED / ANTIQUE
	OCTAGON	8", 12"	UNSEALED, SEALED STAINED / ANTIQUE
	SAN FELIPE	12" x 12"	UNSEALED, SEALED STAINED / ANTIQUE MAGNESE
	HEXAGON	4", 6", 8", 12"	UNSEALED, SEALED STAINED / ANTIQUE
	WALL BASE	4" x 12"	UNSEALED, SEALED
	STAIR COPING	12"	UNSEALED, SEALED STAINED / ANTIQUE
	BRICK	4" x 8", 3" x 12"	UNSEALED, SEALED STAINED / ANTIQUE
		9" x 12"	UNSEALED, SEALED
	RED SELECT	12" x 12"	UNSEALED, SEALED
	CROSS	6"	UNSEALED, SEALED STAINED / ANTIQUE

DESCRIPTION

Salttillo tiles are sourced exclusively from Saltillo, Coahuila, Mexico. They are produced of pure natural clay and are 100% handmade. Saltillo tiles are available in many shapes and sizes, ranging from 4 inch hexagons to 18" squares. Due to the handmade production process, Saltillo tiles vary in size and thickness from piece to piece. This product is also rated high in color variation. It's an authentic terra-cotta artisanal craft-good. From kitchen backsplashes to patio floors, Saltillo tiles work well in almost any application.

RECOMMENDED USE

- Suitable for indoor applications such as kitchen backsplashes and light residential floors.
- Good for bathroom floors.
- Good for outdoor covered areas.
- Suitable for fireplace surrounds and decorative walls.
- This tile is not frost proof.
- This tile should not be used in pools/fountains.

TECHNICAL

- Water Absorption: > 7%
- Abrasive Resistance: PEI 2
- Scratch Hardness: MOHS 4
- Coefficient of Friction (COF): C2
- Shade Variation: V4 (High)